

# **SULFURIC ACID 93%**

## **GUARANTEED ANALYSIS**

Sulfur (S) ..... Derived from Sulfuric Acid.

Weight per gallon: 15.33 lbs per gallon @ 68° F



DANGER CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. MAY CAUSE CANCER.

**PRECAUTIONARY STATEMENTS:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe fumes / gas / mist / vapors / spray. Wash thoroughly after handling. Specific treatment see First Aid section on this label. If exposed or concerned get medical advice / attention.

PERSONAL PROTECTIVE EQUIPMENT: Wear protective gloves / protective clothing / eye protection / face protection. Wash contaminated clothing before reuse. FIRST AID: Immediately call a poison center / doctor. IF SWALLOWED Rinse mouth. Do NOT induce vomiting. IF ON SKIN OR HAIR Take off immediately all contaminated clothing. Rinse skin with water / shower. IF INHALED Remove person to fresh air and keep comfortable for breathing. IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. STORAGE AND DISPOSAL: STORAGE Store

locked up. **DISPOSAL** Dispose of contents / container in accordance with all applicable federal, state, and local regulations.

## PHYSICAL CHARACTERISTICS

Appearance Cl	ear, colorless to cloudy
Weight per gallon @ 6	8°F15.4 lbs.
Gallons per ton	130 gal.
Specific Gravity @ 68°	° <b>F</b> 1.84
Solubility in waterComplete (Exothermic)	
pH	
J.R. SIMPLOT COMPANY	

#### J.R. SIMPLOT COMPANY AgriBusiness P.O. Box 70013, Boise, ID 83707 • (208) 336-2110 GUARANTOR P.O. Box 198, Lathrop, CA 95330

## CONSTRUCTION OF STORAGE & TRANSFER EQUIPMENT

- 1. Tanks and vessels must be rubber lined or constructed of stainless steel or fiberglassreinforced polyester. Mild steels, aluminum and many non-stainless alloys are not satisfactory materials of construction. Stainless steel must be at least 316L or alloy 20 stainless steel.
- 2. Pumps, piping, valves, etc., should be 316L or alloy 20 stainless steel.

### USES

 This product is intended for use on alkaline soils to adjust the pH of targeted soils. Consult with local Agricultural Extension Service or Crop Advisor for rates specific to your soil conditions.

## TRANSPORTATION

Shipments must be shipped RQ, Sulfuric Acid, Class 8, DOT - UN 1830, Packing Group II Corrosive.

Information regarding the contents and levels of metals in this product is available on the Internet at http://www.regulatory-info-jr.com

on the Internet at http://www.regulatory-into-jr.com DISCLAIMER OF WARRANTIES: Seller warrants that the composition of this product conforms to the description given on this label. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES AND REPRESENTATIONS EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE. Timing, rate and method of application, weather and crop conditions, mixtures not specifically recommended on this label or an accompanying written recommendation, are beyond the control of the seller. Buyer assumes all risks of use, storage and handling of this material not in strict accordance with directions given herewith. Buyer further agrees in the event of damages arising from the use of this product, at buyer's option, as full discharge of seller's liability. No one is authorized to make any other warranty, guarantee or directions concerning this product, and no such warranties, guarantees or directions shall be valid or binding upon seller.

Warning: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. Proposition 65, the Safe Drinking Water and Toxic EnforcementAct of 1986, requires notification of potential exposure to substances identified by the State of California as causing cancer, birth defects or other reproductive harm.