VitiSeal™ is a waterborne co-polymer emulsion containing natural plant oils designed to be applied shortly after pruning to provide a sealant barrier over plant pruning wounds. Safely and easily painted or sprayed onto vines, trunks and tree bases, VitiSeal™ is low odor, very low VOC (volatile organic compound), and contains no HAP's (hazardous air pollutants) or known aquatic pollutants. VitiSeal may be used on grapes, cherries, peaches, almonds, pistachios and other woody plants.

Directions for Use: VitiSeal™ ready to use (RTU) solution can be safely painted on cut spurs or wounds at an application volume of approximately 1/2 gallon per acre. Keep product agitated and in solution while using. Under normal temperatures and conditions, the applied solution will dry within 1-2 hours and form a sealant barrier to promote wood and vine wound healing. Optimum application ambient air temperatures are between 50° and 85° F. Do not apply when rain or a significant drop in temperature is expected. Allow for adequate drying conditions.

Clean-Up: Clean tools and equipment while they are still wet with a safe all purpose cleaner and warm water. Flush spray equipment immediately after use. Dry coating may have to be stripped off equipment with a stronger chemical.

Re-application: Re-application is not expected to be necessary until next season pruning. If desired, however, Vi-tiSeal™ may be reapplied any time, conditions permitting, 24 hours or more after initial application and before bud break.

Limitations: Do not mix with oils, solvents or any material except water. Do not contaminate. Store in airtight containers. Do not use in rainy weather, when rain is expected, or when ambient temperature is below 50°F. Keep from freezing.

Storage and Disposal: As with all coatings, keep container tightly closed and out of the reach of children. Protect product from freezing and high temperatures. Dispose of container and unused product in accordance with local environmental regulations.

Typically empty container may be rinsed and placed in trash or appropriate recycling receptacle.

Contents: Waterborne acrylic co-polymer emulsion and natural plant oils.

Health Precautions: No known hazards to humans, domestic animals, wildlife or soil environment. However, this product is not intended for application to humans or animals. Do not ingest. Wear a painter's or similar mask while spraying, and avoid contact with skin and eyes. In the event of eye contact, flush with water for 15 minutes. Remove contact lens. For skin contact, wash with mineral oil, wipe off excess, then wash with soap and water. Get medical attention if irritation persists. See MSDS for further safety information.

Limited Warranty: Product is warranted not to be defective when properly applied. Liability express or implied is limited to replacement of product or refund of purchase price and does not include liability for labor costs or consequential damages. Variable factors out of manufacturer's control, such as environmental conditions, application techniques, and surface conditions are critical to results obtained. Users are expected to exercise reasonable care to determine suitability of the product for each application. This limited warranty is in lieu of all other warranties, express or implied, except as may be required by law. This limited warranty may not be modified or extended by manufacturer's representatives or distributors or dealers of this product.

Produced in the USA by VitiSeal International, LLC. Safecoat® is a registered trademark used under license from American Formulating & Manufacturing. AFM manufactures a complete line of people and planet safe paints, stains, specialty ozaitings and sealers. For additional product information, contact info@witiseal.com.

