

STRION® LED RECHARGEABLE FLASHLIGHT



Case Material 6000 series machined aircraft aluminum with anodized finish

Dimensions Length: 5.90 in. (14.99 cm) Head Diameter: 1.25 in. (3.18 cm) Head Diameter at Tri-Lobe Anti-Roll Flange: 1.44 in. (3.66 cm) Barrel Diameter: 0.95 in. (2.41 cm)

Weight 5.22 oz (148 grams) with battery Lens Borofloat high temperature glass lens

Light Source C4[®] LED technology, impervious to shock with a 50,000 hour lifetime.

Switch Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable intensity or strobe mode.

Output/Runtime: Three modes and strobe:

- High for a bright super-bright beam - 260 lumens; 10,000 candela peak beam intensity; 200 meter beam distance; runs 2 hours

- Medium for bright light and longer run times - 130 lumens; 5,000 candela peak beam intensity; 141 meter beam distance; runs 4 hours

- Low for light without glare and extended run times - 65 lumens; 2,500 candela peak beam intensity; 100 meter beam distance; runs 7.5 hours

- Strobe for disorienting or signaling your location; runs 5.5 hours

Battery Lithium Ion with on-board safety control circuit, 3.75V, 2200mAh, rechargeable up to 1000 times

Charging Clamp style charge holder with digital control circuit that prevents over charge. Fully recharges battery in 3 hours. Charge base LED indication: LED Steady -Charging; LED Blinking - Charged. Standard or PiggyBack® charger

- Features C4 LED technology for extreme brightness
 - · LED Charge-continuity indicator on charger base; Compact, snap-in charger mounts in any position
 - · IPX4 water resistant operation; 2 meter impact resistance tested
 - · Serialized for positive identification

Approvals Most models meet applicable European Community Directives

Warranty

Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Item #
Strion LED - IEC Type C (230V) AC/12V DC - 2 Holders	080926-74312-0	74312
Strion LED - IEC Type A (120V/100V) AC/12V DC - 2 Holders	080926-74302-1	74302
Strion LED - IEC Type C (230V) AC/12V DC - 1 Holder	080926-74311-3	74311
Strion LED - IEC Type G (240V) AC/12V DC - 1 Holder	080926-74321-2	74321
Strion LED - IEC Type A (120V/100V) AC/12V DC - 1 Holder	080926-74301-4	74301
Strion LED - IEC Type A (120V/100V) AC/12V DC - (1) Holder Clam packaged	080926-74308-3	74308
Pink Strion LED - IEC Type A (120V/100V) AC/12V DC - (1) Holder Clam packaged	080926-74350-2	74350
Strion LED - Grip Ring - IEC Type A (120V/100V) AC	080926-74309-0	74309
Strion LED - IEC Type C (230V) AC	080926-74313-7	74313
Strion LED - IEC Type A (120V/100V) AC	080926-74303-8	74303
Strion LED - 12V DC	080926-74304-5	74304
Strion LED - IEC Type A (120V/100V) AC/12V DC PiggyBack	080926-74353-3	74353
Strion LED (WITHOUT CHARGER)	080926-74300-7	74300

Assembled in USA





