


Electric Track Chargers



Item Name	Solar Charger	Direct Charger
Part #	CHG-SLR740	CHG-AC750
Description	Uses sunlight to supply power to up to 300' of electric track. Completely weatherproof.	Plugs into a regular 110v outlet and supplies power up to 500' of electric track. If outdoors, use Weatherproof Box (see below).
Area of Coverage	300' (91.44 m) of track	500' (152.4 m) of track
Input Voltage	4 VDC	110 - 120VAC
Output Voltage	7.0 KV (+/-) 20% Open Circuit Voltage, Intermittent DC Output	750 V (+/-) 20% Open Circuit Voltage, Intermittent AC Output
Dimensions	9.75" x 6.5" x 6.5" (24.77 cm x 16.51 cm x 16.51 cm)	4.75" x 4.5" x 2.25" (12 cm x 11.5 cm x 5.7 cm)
Weight	3.5 lbs. (1.59 kg)	13.6 oz. (386 g)

INSTALLATION COMPONENTS

Item	Description	Item Number	Pack Size
	Connector Loops Used to attach the copper Lead-In Wire to your charger.	STPWC-10	10
	Bilingual Warning Labels Placed every 10' to warn people of possible shock. (English/Spanish)	BJFTWRNBI-10	10
	Voltage Tester Used with the Electric Track systems to test the systems' output voltage.	BJFT-VLT	1
	Solar Battery Replacement Battery for the Solar Charger (CHG-SLR740) should be replaced about once a year.	CHG-SLR740BAT	1
	Waterproof Box Protects Direct Chargers from weather when installed outdoors. (Dimensions: 8"x8"x4")	CHG-ACBOX	1

14 Gauge Marine Grade Copper Lead-in Wire

Used to connect your charger to the electric track systems and also connect sections of track.

Available in three colors and three roll sizes.



Part #	Length	Color
BJFT-LIW20BLK	20' (6.10 m)	Black
BJFT-LIW50BLK	50' (15.24 m)	Black
BJFT-LIW100BLK	100' (30.48 m)	Black
BJFT-LIW20GRY	20' (6.10 m)	Gray
BJFT-LIW50GRY	50' (15.24 m)	Gray
BJFT-LIW100GRY	100' (30.48 m)	Gray
BJFT-LIW20STN	20' (6.10 m)	Stone
BJFT-LIW50STN	50' (15.24 m)	Stone
BJFT-LIW100STN	100' (30.48 m)	Stone



LEARN TO INSTALL ELECTRIC TRACK

Bird•B•Gone® offers free training for all of our products. Bird•B•Gone® University teaches:

- Site evaluation
- Product selection
- How to install products
- Quoting bird jobs
- How to hang netting
- How to avoid problems
- Troubleshooting

Call us at
1-800-392-6915
for details!