

Super strength. Ultimate ease.

3M™ Dual Lock™ Reclosable Fasteners

Unique mushroom-shaped heads snap shut and stay locked.

- Helps reduce vibration
- Temperature, moisture and UV resistant
- Durable — up to 1,000 openings and closings before losing 50% of original tensile strength
- Pressure-sensitive adhesive easily forms a powerful bond
- Interlocking mushroom-shaped heads have **5X the tensile strength** of hook-and-loop products
- Application and maintenance ease
- Low profile option available — approximately half the thickness of standard fastener



Secure plastic signs
to window glass



Anchor vehicle accessories
to dashboard



Attach elevator control
panel to interior wall



Fasten ceiling panels to
interior for future access



Attach access panels to
industrial, electronic and
electrical equipment

3M™ Dual Lock™ Reclosable Fasteners and Applications

Product	Stem Density (per sq/in)	Adhesive	Color	3M Liner	Engaged Thickness	Temperature Resistance
SJ3540	250	Rubber	Black	White, 5mil (0.13mm) Polyolefin	0.23 in (5.7mm)	120°F (49°C)
SJ3541	400					
SJ3542	170					
SJ3550	250	White Acrylic	Black	Clear, 4mil (0.10mm) Polyolefin	0.23 in (5.7mm)	200°F (93°C)
SJ3551	400					
SJ3552	170					
SJ3558	250	White Acrylic	Clear*	Clear, 4mil (0.10mm) Polyolefin	0.23 in (5.7mm)	200°F (93°C)
SJ3560	250	Clear Acrylic	Clear	Clear, 4mil (0.10mm) Polyolefin	0.23 in (5.7mm)	220°F (104°C)
SJ3561	400					
SJ3562	170					
SJ3550CF	250	Clear Acrylic	Black	Clear, 4mil (0.10mm) Polyolefin	0.23 in (5.7mm)	220°F (104°C)
SJ3551CF	400					
SJ3552CF	170					
SJ3870	250	Modified Acrylic	Black	Red, 4.5mil (0.11mm) Polyolefin	0.24 in (6.1mm)	140°F (60°C)
SJ3871	400					
SJ3872	170					
SJ3782	250	Low Surface Energy Acrylic	Black	Brown, 83# Polykraft	0.16 in (4.1mm)	120°F (49°C)
SJ3440	250	None	Black	No Liner	0.15 in (3.86mm)	220°F (104°C)
SJ3441	400					
SJ3442	170					
SJ3443	400	Non-woven backing with no adhesive	Black	No Liner	0.28 in (7.1mm)	220°F (104°C)
SJ3444	170					
SJ3445	250					
SJ3460	250	None	Clear	No Liner	0.15 in (3.86mm)	220°F (104°C)
SJ3463	400	Piece Part Circle†	Black	No Liner	0.20 in** (5.1mm)	220°F (104°C)
SJ3481	400	Rigid Strip†	Black	No Liner	0.20 in** (5.1mm)	220°F (104°C)
SJ4570	Low Profile/Thin	Low Surface Energy Acrylic	Clear	Brown, 83# Polykraft	0.098 in (2.489mm)	158°F (70°C)
SJ4575			Black			
SJ4580		Clear Acrylic	Clear	Red, 4.5mil (0.11mm) Polyolefin	0.12 in (3.0mm)	200°F (93°C)

*Clear fastener utilizes a white adhesive giving the product a white appearance

**Single thickness; not engaged

†No adhesive

Substrates					Use	Markets						
Metals (Al & SS)	Glass	Plastics (Acrylic, PC, ABS)	Powder Coated Paints	Low Surface Energy (PP, PE)	Indoor/Outdoor	Aerospace & Rail	Appliance & Electronics	Design & Construction	Furniture & Upholstery	General Industrial	Marine & Specialty Vehicle	POP, Display & Signage
■		■	■	■	Indoor				■	■		■
■	■	■	●	●	Indoor/Outdoor	■	■	■	■	■	■	■
■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■
■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■
■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■
■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■
■		■	■	●	Indoor/Outdoor				■	■		■
■		■	■	■	Indoor/Outdoor		■		■	■		■
▲	▲	▲	▲	▲	Indoor/Outdoor		▲	▲	▲	▲	▲	▲
▲	▲	▲	▲	▲	Indoor/Outdoor		▲	▲	▲	▲	▲	▲
▲	▲	▲	▲	▲	Indoor/Outdoor		▲	▲	▲	▲	▲	▲
■		■	■	■	Indoor/Outdoor		■	■	■	■	■	■
▲	▲	▲	▲	▲	Indoor/Outdoor		▲	▲	▲	▲	▲	▲
■		■	■	■	Indoor/Outdoor		■	■	■	■	■	■
■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■



- Best Suggested Product
- Primer Recommended
- ▲ Performance Dependent on the Selected Attachment Method


Many of our 3M™ Dual Lock™ Reclosable Fasteners feature 3M™ VHB™ Tape which adds extraordinary holding power and aging properties through a range of environmental impacts; non-adhesive product also available.

Mix and match stem densities (stems per square inch) to customize for the strength requirements of your project.

Stem Density (per sq/in) Combinations

Strongest	250:400
Stronger	250:250 or 170:400
Strong	170:250
Not Recommended	170:170 or 400:400

Interchangeable Strength Combinations



Type 400

Type 250

Type 170

Low Profile

Self-Mating

