

Gauges



Order Information

2-1/2" Stainless Steel, Liquid Filled, Brass Internals, 1/4" Bottom Stem

Graduation				
Part Number	Number	Major	Minor	PSI Range
GG30	5	5	1	0-30
GG60	10	10	2	0-60
GG100	10	10	2	0-100
GG160	20	20	5	0-160
GG200	20	20	5	0-200
GG300	50	50	10	0-300
GG400	50	50	10	0-400
GG600	100	100	20	0-600
GG1000	200	100	20	0-1000
GG1500	300	300	50	0-1500
GG2000	200	200	50	0-2000
GG3000	500	500	100	0-3000
GG4000	500	500	100	0-4000
GG5000	1000	1000	100	0-5000
GG6000	1000	1000	200	0-6000
GG10000	2000	2000	200	0-10000
GG15000	3000	3000	500	0-15000



Part Number	PSI	BAR
2640-0009	0-60	4
2640-0010	0-100	7
2640-0011	0-200	14
2640-0007	0-300	21
2640-0008	0-600	42
2640-0001	0-1000	70
2640-0002	0-1500	105
2640-0003	0-2000	140
2640-0004	0-3000	210
2640-0005	0-5000	350
2640-0014	0-10000	700
2640-0006	30" Hg/ 30 psi/1x2	-
2640-0015	30" Hg/ 100 psi/1x2	-



Series GG

304 stainless steel case, bronze tube, brass stem and internals, white enameled aluminum dial face, black enameled aluminum pointer, acrylic window, liquid filled, built-in restrictor.

Order Information

1/4" Bottom Stem

Graduation				
Part Number	Number	Major	Minor	PSI Range
GG604	10	10	2	0-60
GG1004	10	10	2	0-100

Order Information

2-1/2" Stainless Steel, Liquid Filled, Brass Internals, 1/4" Center Back Mount

Graduation				
Part Number	Number	Major	Minor	PSI Range
WGG60C	10	10	2	0-30
WGG100C	10	10	2	0-60
WGG160C	20	20	2	0-100
WGG200C	20	20	5	0-160
WGG300C	50	50	10	0-200
WGG400C	50	50	10	0-300
WGG600C	50	50	20	0-400
WGG1000C	100	100	20	0-600
WGG1500C	100	100	50	0-1000
WGG2000C	300	300	50	0-1500
WGG3000C	200	200	100	0-2000
WGG5000C	500	500	100	0-3000
WGG10000C	1000	1000	200	0-4000
WGG15000C	3000	3000	500	0-6000

Includes Clamp

Glycerin-Filled Pressure Gauge

This series is designed for use with air, gas, oil, and water or any medium not corrosive to brass or bronze. Liquid-filled gauges are recommended for reducing shock waves caused by pressure or vibration fluctuations.

- Movement: Brass
- Bourdon Tube: Phosphor bronze
- Pointer: Black-enameled aluminum
- Dial: White background
- Window: Acrylic
- Liquid Fill: 99.5% pure virgin Glycerin
- Connection: 1/4" NPT Brass connection
- Accuracy: ASME/ANSI B40.1 Grade B (3-2-3%)

Standard Gauge Dampner

Stem size: 1/4" (M) NPT, 1/4" (F) NPT

Order Information

Model Number	2404-0047
--------------	-----------