

# Accessories



### Pressure Switch

- Max. Pressure: 3500 psi
- Max. Temp: 200 °F
- Voltage: 12-250 V
- Max. Amp vertical and horizontal mount: 15A
- 3/8" (M) NPT inlet

#### Order Information

Model Number	2510-0029
--------------	-----------



### Float Switch

- Max. Pressure: 3500 psi
- Max. Flow: 7.8 gpm
- Max. Temp: 180 °F
- Voltage: 12-250 V

#### Order Information

Model Number	Mount	Inlet	Outlet
2510-0030	Vertical	3/8" (F)	3/8" (F)
2510-0031	Horizontal	3/8" (M)	3/8" (M)



### Aluminum Line Strainer

- Max. pressure: 100 psi
- Max. flow: 8 gpm
- 1/2" BPS (F) inlet; 1/2" BPS (M) outlet
- Aluminum housing
- 50 mesh screen
- Added bypass hose port G 1/4"

#### Order Information

Model Number	3350-0134
--------------	-----------



### Suction Strainer

#### Order Information

Model Number	Size	Mesh	Material	Opening Size	Overall Dia.
3350-0021	1/4" (ID) plastic tubing	50 mesh	ss screen	(D) .330"	1.25"
3350-0022	1/4" (ID) plastic tubing	50 mesh	ss screen	(D) .330"	1.00"
3350-0033	5/8" (ID) x 61/64" (OD) garden hose	50 mesh	ss screen	(D) .940"	2.187"
3800-0035	(F) garden hose end	50 mesh	ss screen	-	-

### Chemical Injector Strainer

#### Plastic

- Chemical-resistant plastic body and components
- 1/4" and 3/8" hose barb
- Check valve optional

#### Stainless Steel

- Corrosion-resistant stainless steel and brass construction
- 1/4" hose barb
- Check valve standard

#### Order Information

##### For 2200 & 2300 PowerLine PLUS Pumps

Model Number	Material	Description
3350-0126	Plastic	with check valve
3350-0127	Plastic	without check valve
3350-0128	Stainless Steel	with check valve

