








| Straining Wire | Size | Description | Details | Item Number | Pack Size |
|---|--|---|---|--|--|
|  | 3/32" (2.38 mm) For jobs OVER 50' in length | A perimeter cable to support your netting installation. Use galvanized cable for normal areas of installation. | 3/32" Diameter, 7 x 7 Stranded Construction Cable | BNSW500G332 BNSW250G332 BNSW500S332 BNSW250S332 | 500' (152.40 m) Galvanized 250' (76.20 m) Galvanized 500' (152.40 m) Stainless Steel (316) 250' (76.20 m) Stainless Steel (316) |
| | 1/16" (1.59 mm) For on jobs UNDER 50' in length | Use 316 grade stainless steel cable for areas near salt water, chemicals, etc. | 1/16" Diameter, 7 x 7 Stranded Construction Cable | BNSW500G116 BNSW250G116 BNSW500S116 BNSW250S116 | 500' (152.40 m) Galvanized 250' (76.20 m) Galvanized 500' (152.40 m) Stainless Steel (316) 250' (76.20 m) Stainless Steel (316) |

| Fasteners | Item | Description | Details | Item Number | Pack Size |
|--|--|--|--|--|---|
|  | Cable Clamps An alternative method of securing cable (instead of ferrules). | Use galvanized cable clamps for normal installation. Use stainless steel cable clamps for areas near salt water or chemicals, etc. | Runs up to 100' (30.48 m): Use two (2) clamps Runs over 100' (30.48 m): Use three (3) clamps | BNCC-G BNCC-S* | Cable Clamps Galvanized (10/pk) Cable Clamps Stainless (10/pk) |
|  | Ferrules Used to clamp down and secure your straining wire at the ends. | Use aluminum ferrules with galvanized cable. Use copper ferrules with stainless steel cable. For use with Bird Net Ratchet Crimp Tool (pg. 23). | Use 3/32" ferrules with 3/32" cable Use 1/16" ferrules with 1/16" cable | BNF332A* BNF116A* BNF332C* BNF116C* | 3/32" (2.38 mm) Aluminum (100/pk) 1/16" (1.58 mm) Aluminum (100/pk) 3/32" (2.38 mm) Copper (100/pk) 1/16" (1.58 mm) Copper (100/pk) |
|  | M6 M8 Turnbuckles Used to tighten straining wire to prevent sagging or drooping. | Use galvanized turnbuckles with galvanized wire and aluminum ferrules. Use stainless steel turnbuckles and wire with copper ferrules for installations near salt water, chemicals, etc. | Cable runs under 25' (7.62 m): M5 turnbuckles Cable runs of 25' - 75' (7.62 m - 22.86 m), use M6 turnbuckles Cable runs over 75', use M8 turnbuckles | BNGTS (10/pk) BNGTM (10/pk) BNGTL (10/pk) BNSSTS (10/pk)* BNSSTM (10/pk)* BNSSTL (10/pk)* | M5 Small Galvanized Turnbuckle M6 Medium Galvanized Turnbuckle M8 Large Galvanized Turnbuckle M5 Small Stainless Steel Turnbuckle M6 Medium Stainless Steel Turnbuckle M8 Large Stainless Steel Turnbuckle |

| Corner Attachments | Item | Description | Details | Item Number | Pack Size |
|---|--|---|--|--|--|
|  | Net Bolts High load bearing expansion bolts used as corner attachments for masonry, concrete or stone. | Use galvanized Net Bolts with galvanized wire Use stainless steel Net Bolts with stainless steel wire Drill Bits (p.24) M6: 10 mm drill bit M8: 13 mm drill bit | Use M6/Medium Net Bolts for cable runs under 100' (30.48 m) Use M8/Large Net Bolts for cable runs over 100' (30.48 m) | BNM6EB (10/pk) BNM6SSEB (10/pk) BNM8EB (10/pk) | M6 Medium Net Bolt Galvanized M6 Medium Net Bolt Stainless Steel M8 Large Net Bolt Galvanized |
|  | Girder Clamp Used to attach netting to girders. | Can also be used as an intermediate attachment Attach bolt onto flat steel or I-beam | For steel up to 3" (7.62 cm) thickness Can be used as corner attachments if drilling is not an option. | BNGCL-3 | Girder Clamp - up to 3" (7.62 cm) (10/pack) |
|  | Mini-Net Bolt Corner attachment used for cable runs of less than 20' (6.09 m). | Use galvanized Net Bolts with galvanized wire Use stainless steel Net Bolts with stainless steel wire Drill Bits (p.24): 8 mm drill bit | Use M6/Medium Net Bolts for cable runs under 100' (30.48 m) Use M8/Large Net Bolts for cable runs over 100' | BNMNB-G BNMNB-S | Mini-Net Bolt Galvanized (10/pack) Mini-Net Bolt Stainless Steel (10/pack) |
|  | Eye Bolt w/ Nut Corner attachment for steel I-beams or other thick metals. | Drill Bits (p.24): 8 mm drill bit | Use galvanized Eye Bolts w/ galvanized wire Use stainless steel Eye Bolts w/ stainless steel wire | BNGEB-NUT BNSEB-NUT* | Galvanized Eye Bolt w/Nut (20/pk) Stainless Steel Eye Bolt w/Nut (10/pk) |
|  | Screw Eyes Used as a corner attachment into wood. | Use Large Screw Eyes for runs over 20' (6.1 m) Use Small Screw Eyes for runs under 20' (6.1 m) | Use galvanized with galvanized wire Use stainless steel with stainless steel wire | BNLSE-G (100/pk) BNLSE-S (20/pk)* BNSSE-G (100/pk) BNSSE-S (20/pk)* | Large Wood Screw Eye Galvanized Large Wood Screw Eye Stainless Steel Small Wood Screw Eye Galvanized Small Wood Screw Eye Stainless Steel |

*Available in 316 steel upon request