







Straining Wire	Size	Description	Details	Item Number	Pack Size
	3/32" (2.38 mm)	A perimeter cable to support your netting installation. Use galvanized cable for normal areas of installation.	3/32" Diameter, 7 x 7 Stranded Construction Cable	BNSW500G332	500' (152.40 m) Galvanized
				BNSW250G332	250' (76.20 m) Galvanized
				BNSW500S332	500' (152.40 m) Stainless Steel (316)
				BNSW250S332	250' (76.20 m) Stainless Steel (316)
	1/16" (1.59 mm)	Use 316 grade stainless steel cable for areas near salt water, chemicals, etc.	1/16" Diameter, 7 x 7 Stranded Construction Cable	BNSW500G116	500' (152.40 m) Galvanized
				BNSW250G116	250' (76.20 m) Galvanized
				BNSW500S116	500' (152.40 m) Stainless Steel (316)
				BNSW250S116	250' (76.20 m) Stainless Steel (316)

Fasteners	Item	Description	Details	Item Number	Pack Size
	Cable Clamps An alternative method of securing cable (instead of ferrules).	Use galvanized cable clamps for normal installation.	Runs up to 100' (30.48 m):	BNCC-G BNCC-S*	Cable Clamps Galvanized (10/pk) Cable Clamps Stainless (10/pk)
		Use stainless steel cable clamps for areas near salt water or chemicals, etc.	Use two (2) clamps Runs over 100' (30.48 m): Use three (3) clamps		
	Ferrules Used to clamp down and secure your straining wire at the ends.	Use aluminum ferrules with galvanized cable.	Use 3/32" ferrules with 3/32" cable	BNF332A*	3/32" (2.38 mm) Aluminum (100/pk)
		Use copper ferrules with stainless steel cable.	Use 1/16" ferrules with 1/16" cable	BNF116A*	1/16" (1.58 mm) Aluminum (100/pk)
		For use with Bird Net Ratchet Crimp Tool (pg. 23).		BNF332C*	3/32" (2.38 mm) Copper (100/pk)
				BNF116C*	1/16" (1.58 mm) Copper (100/pk)
	M6 M8 Turnbuckles Used to tighten straining wire to prevent sagging or drooping.	Use galvanized turnbuckles with galvanized wire and aluminum ferrules.	Cable runs under 25' (7.62 m): M5 turnbuckles	BNGTS (10/pk)	M5 Small Galvanized Turnbuckle
		Use stainless steel turnbuckles and wire with copper ferrules for installations near salt water, chemicals, etc.	Cable runs of 25' - 75' (7.62 m - 22.86 m), use M6 turnbuckles Cable runs over 75', use M8 turnbuckles	BNGTM (10/pk) BNGTL (10/pk) BNSSTS (10/pk)* BNSSTM (10/pk)* BNSSTL (10/pk)*	M6 Medium Galvanized Turnbuckle M8 Large Galvanized Turnbuckle M5 Small Stainless Steel Turnbuckle M6 Medium Stainless Steel Turnbuckle M8 Large Stainless Steel Turnbuckle

Corner Attachments	Item	Description	Details	Item Number	Pack Size
	Net Bolts High load bearing expansion bolts used as corner attachments for masonry, concrete or stone.	Use galvanized Net Bolts with galvanized wire	Use M6/Medium Net Bolts for cable runs under 100' (30.48 m)	BNM6EB (10/pk)	M6 Medium Net Bolt Galvanized
		Use stainless steel Net Bolts with stainless steel wire	Use M8/Large Net Bolts for cable runs over 100' (30.48 m)	BNM6SSEB (10/pk) BNM8EB (10/pk)	M6 Medium Net Bolt Stainless Steel M8 Large Net Bolt Galvanized
	Girder Clamp Used to attach netting to girders.	Can also be used as an intermediate attachment	For steel up to 3" (7.62 cm) thickness	BNGCL-3	Girder Clamp - up to 3" (7.62 cm) (10/pack)
		Attach bolt onto flat steel or I-beam	Can be used as corner attachments if drilling is not an option.		
	Mini-Net Bolt Corner attachment used for cable runs of less than 20' (6.09 m).	Use galvanized Net Bolts with galvanized wire	Use M6/Medium Net Bolts for cable runs under 100' (30.48 m)	BNMNB-G BNMNB-S	Mini-Net Bolt Galvanized (10/pack) Mini-Net Bolt Stainless Steel (10/pack)
		Use stainless steel Net Bolts with stainless steel wire	Use M8/Large Net Bolts for cable runs over 100'		
	Eye Bolt w/ Nut Corner attachment for steel I-beams or other thick metals.	Drill Bits (p.24): 8 mm drill bit	Use galvanized Eye Bolts w/ galvanized wire	BNGEB-NUT	Galvanized Eye Bolt w/Nut (20/pk)
			Use stainless steel Eye Bolts w/ stainless steel wire	BNSEB-NUT*	Stainless Steel Eye Bolt w/Nut (10/pk)
	Screw Eyes Used as a corner attachment into wood.	Use Large Screw Eyes for runs over 20' (6.1 m)	Use galvanized with galvanized wire	BNLSE-G (100/pk)	Large Wood Screw Eye Galvanized
		Use Small Screw Eyes for runs under 20' (6.1 m)	Use stainless steel with stainless steel wire	BNLSE-S (20/pk)* BNSSE-G (100/pk) BNSSE-S (20/pk)*	Large Wood Screw Eye Stainless Steel Small Wood Screw Eye Galvanized Small Wood Screw Eye Stainless Steel

*Available in 316 steel upon request