



Model 25660

Features:

- Interchangeable nozzle tips are color-coded for easy identification of nozzle tip size.
- Nozzle tips provide a 45° full cone "showerhead" spray pattern.
- Convenient trigger lock for continuous spraying.

- Options available: hose shank swivel for inlet connection and extension wand and adapters for low-volume and spot spraying.
- Maximum operating pressure of 200 PSI (14 bar).
- Made of Nylon with Viton® O-rings and stainless steel springs.

| MODEL NUMBER | NOZZLE TIP NUMBER | CAPACITY (GPM) AT VARIOUS PRESSURE* | | | | | | |
|--------------|-------------------|-------------------------------------|-------|-------|-------|--------|--------|--------|
| | | 2 PSI | 4 PSI | 6 PSI | 8 PSI | 10 PSI | 15 PSI | 20 PSI |
| 25660-1.5 | CP25670-1.5-NY | 1.4 | 1.9 | 2.3 | 2.6 | 2.9 | 3.4 | 4.0 |
| 25660-3.0 | CP25670-3.0-NYB | 2.0 | 2.7 | 3.2 | 3.6 | 4.1 | 4.9 | 5.6 |
| 25660-4.0 | CP25670-4.0-NY | 2.3 | 3.1 | 3.7 | 4.3 | 4.7 | 5.6 | 6.4 |

*Pressure measured at spray nozzle.



25660 TeeJet Lawn Spray Gun

25990 Swivel

Allows operator to concentrate on application without hose interference. 3/4" (M) NPT connection with 1/2" hose shank. Maximum pressure 150 PSI (10 bar).

25657-NYB Adapter

Replaces shower nozzle to allow extension wand or standard TeeJet tip to be attached directly to lawn spray gun. 3/4" (F) GHT inlet with 1/4"-16 TeeJet thread outlet. Maximum pressure 150 PSI (10 bar). See page 134 for adjustable ConeJet® nozzles.

22665 Extension Wand

For low volume and spot spraying applications. Available in both 15" and 24" (38 cm and 61 cm) lengths, the extension fits on 25657-NYB adapter. Maximum pressure 150 PSI (10 bar).

CP22673-PP & CP22664-PP Adapters

Used for attaching standard TeeJet tips or adjustable ConeJet nozzles. See page 134 for adjustable ConeJet nozzles.