

INTERMEDIATE ATTACHMENTS

| | ITEM | DESCRIPTION | DETAILS | ITEM # | PACK SIZE |
|--------------------|--|--|--|---|---|
| • | NET MAGNET | 40 lb. pull strength ceramic magnet in steel casing. Best for smaller jobs. | For easy and secure attachment for various types and sizes of hardware when drilling is not possible | BN200MGNT | 2" (3.18 cm) Net Magnet (10/pk) |
| 4 | MULTI- PURPOSE CABLE BRACKET WITH HILTI PIN | Used to secure cable around the perimeter of the net installation. Can be installed for permanent installation or easy release | For attaching to concrete or steel. (Hilti Gun required) Use with BNHS-27 | BNMPCB- 125HP-C BNMPCB-12 5HP-S | 1.25" (3.18 cm) Bracket w/ Hilti pins for concrete (100/ pk) 1.25" (3.18 cm) Bracket w/ Hilti pins for steel (100/pk) |
| | MULTI- PURPOSE CABLE BRACKET | Used to secure cable around the perimeter of the net installation | Can be used for permanent installation by running cable through bracket hole or easy release by running cable through hook | BNMPCB125-100 | 1.25" (3.18 cm) Bracket (100/ pk) |
| | NET SPIKES | Used to secure netting into concrete Drill Bits Large Net Spike: 6.5 mm Small Net Spike: 5.0 mm | Small net spikes have a bend in the body Large net spikes will "flange" out when hammered | BNNS-SM BNNS-LG* | Bird Net 3/16" (4.76 mm) Diameter Small Spike (100/pk) Bird Net 1/4" (6.35 mm) Diameter Large Spike (100/pk) |
| | LAG SCREWS | Used to secure cable around the perimeter of a net installation | Lag Screws are ideal for concrete, stucco, and wood Use Anchor for extra support when using small Lag Screws | BNLS-SSM* BNLS-LGG* BNLS-ASM | Small Steel Lag Screw (100/pk) Large Galvanized Lag Screw (100/pk) Small Lag Screw Anchor (100/pk) |
| & & | GIRDER CLIPS | Designed to attach cable to I-beams or steel surfaces 100 per pack | Clips hammer directly onto the I-beam to secure the cable Zinc coated spring steel attachments come in 4 widths | BN116GC BN018GC BN014GC BN012GC | Girder Clip: 1/16" - 1/8" (1.59mm - 3.1mm) Girder Clip: 1/8" - 1/4" (3.17mm - 6.35mm) Girder Clip: 1/4" - 1/2" (6.35mm - 12.7mm) Girder Clip: 1/2" - 3/4" (12.7mm - 19.05 mm) |
| کے کے | S-CLIPS | S-Clips are secured to the perimeter surface on one end and straining wire is strung through the other | Made of durable 316 stainless steel to hold up in the toughest environments Hilti pin available for concrete or steel | BNMSCLP BNMSCLP-PIN-C BNMSCLP-PIN-S | S-Clip (100/pack) S-Clip w/Hilti Pin for concrete (100/pk) S-Clip w/Hilti Pin for steel (100/pk) |
| 2 | THIN WIRE NET CLIP | Ideal for small net installations that require the net to be removed | Stainless steel intermediate attachment | BNTWNC-1 | Thin Wire Net Clip (100/ pack) |
| 6 | STAINLESS STEEL NET LOOP | Ideal for wood and sheet metal | To secure, use self tapping sheet metal screws or wood screws | BNNL | Bird Net Loop (100 per pack) |
| | SPLIT PINS AND ANCHOR RIVETS | Used on stone or brick surfaces 100 per pack | Low profile intermediate attachment Available in two sizes Use 6.5 mm drill bit | BN10R BN10SP BN15R BN15SP | 1" (2.54 cm) Rivet (100/pk) 1" (2.54 cm) Stainless Steel Split Pin (100/pk) 1.5" (3.81 cm) Rivet (100/pk) 1.5" (3.81 cm) Stainless Steel Split Pin (100/pk) |
| | 2" HEAVY DUTY STEEL CLAMP | Designed for large installations and creates a strong hold on steel and l-beams | Holds straining wire to steel 2" opening Jaw strength supports up to 630 lbs. 4 per pack | BNBCLP-2 | 2" (5.08 cm) Heavy Duty Steel Clamp (4/pk) |
| 1 | 6" ROOF TILE BRACKET | Used to install netting on roofs that have tiles | Slides underneath the tile to create a bracket for netting cables | BNRTB-600 | 6" (15.24 cm) Roof Tile Bracket (10/pack) |